



SPECIFICATION SHEET FOR BANWEAR style BW700-T

FABRIC:	BANWEAR® STYLE BW700-T 88% COTTON / 12% NYLON TWILL
WIDTH:	60/61"
THREAD COUNT:	94 X 50 THREADS PER SQUARE INCH
WEIGHT: (ASTM D3776-96)	7.0 oz. PER SQ. YARD (Minimum)
BREAKING STRENGTH: (ASTM D5034)	100 lbs. WARP (Minimum) 60 lbs. FILL (Minimum)
TEARING STRENGTH: (ASTM D1424)	4.0 x 4.0 lbs. (Minimum)
SHRINKAGE: (AATCC 96-1997)	5.0% MAXIMUM WARP AND FILL
FLAMMABILITY:	FTM 191.5903 ASTM D 6413
AFTER FLAME:	2.0 SECONDS
CHAR LENGTH:	4.0 INCHES (Maximum)
ARC RATING: (ASTM F1959)	9.6 Cal/cm ²
CARE INSTRUCTIONS:	MACHINE WASH HOT WITH DETERGENT NO CHLORINE BLEACH — NO SOAP TUMBLE DRY WARM DRY CLEANABLE

THIS FABRIC MEETS THE INDUSTRY STANDARDS AS OUTLINED IN
ASTM F1506, NFPA70E HRC/2, NFPA2112, and OSHA 29 CFR 1910.269

*PROVIDED THE CARE INSTRUCTIONS ARE PROPERLY FOLLOWED, THE FINISH
IN THIS FABRIC IS DESIGNED TO LAST THE USABLE LIFE OF THE GARMENT*



ITEX, Inc. is an ISO 9001:2008 Certified Company