



SPECIFICATION SHEET FOR BANOX FR3® style BX900-S

FABRIC:	BANOX FR3® STYLE BX900-S 100% COTTON SATEEN
WIDTH:	60/61"
THREAD COUNT:	90 X 48 THREADS PER SQUARE INCH
WEIGHT: (ASTM D3776-96)	9.0 oz. PER SQ. YARD (Minimum)
BREAKING STRENGTH: (ASTM D5034)	110 lbs. WARP (Minimum) 70 lbs. FILL (Minimum)
TEARING STRENGTH: (ASTM D1424)	6.0 x 6.0 lbs. (Minimum)
SHRINKAGE: (AATCC 96-1997)	6.0% MAXIMUM WARP AND FILL
FLAMMABILITY:	FTM 191.5903 ASTM D 6413
AFTER FLAME:	2.0 SECONDS
CHAR LENGTH:	4.0 INCHES (Maximum)
ARC RATING: (ASTM F1959)	9.1 Cal/cm ²
CARE INSTRUCTIONS:	MACHINE WASH HOT WITH DETERGENT NO CHLORINE BLEACH — NO SOAP TUMBLE DRY WARM DRY CLEANABLE

THIS FABRIC MEETS THE INDUSTRY STANDARDS AS OUTLINED IN
ASTM F1506, NFPA70E HRC/2, NFPA701, and OSHA 29 CFR 1910.269

PROVIDED THE CARE INSTRUCTIONS ARE PROPERLY FOLLOWED, THE FINISH IN THIS
FABRIC IS DESIGNED TO LAST UP TO 25 INDUSTRIAL AND 50 HOME LAUNDERINGS

ITEX, Inc. is an ISO 9001:2008 Certified Company

